



Screen Chemicals



AUXILIARIES – PERMANENT ADHESIVES

ADHESIVES FOR TABLES, CARPETS AND PALLETS FOR TEXTILE PRINTING

ADESIVO AM 10 W

Code 163515

Water-based permanent adhesive for tables, carpets and pallets for textile printing.

PROPERTIES:

- Indicated for heavy fabrics and plush
- Water resistant

PREPARATION:

Dilute the product with water.

APPLICATION:

- Mix well the mixture, before using it.
- Apply the mixture through a brush, a roller or by spraying it.
- Once the product is applied, let it dry at room temperature.
- Wash the used tools with water immediately after use.
- The adhesive may be removed through **SOLVENTE 505**.

Package: 1 and 5 Kg

SCRCHE ADHESIVE

Codice 991088

Water-based permanent adhesive for tables and pallets for textile printing.

PROPERTIES:

- Ideal when FLASH IR lamps or intermediate drying are used
- Washable with water to clean the fabric remains

PREPARATION:

Ready to use. Can be diluted with up to 20% of water to decrease viscosity, **this entails the reduction of adhesion.**

APPLICATION:

- Mix the mixture well, before using it.
- Apply the mixture through a brush, a roller or by spraying it.
- Once the product is applied, let it dry at room temperature to avoid that adhesive may transfer on the fabric background
- Wash the used tools with water immediately after use.
- In order to remove the adhesive, it is recommended the use of **SOLVENTE 505**.

Package: 5 Kg

SPECIAL INSTRUCTIONS

- Always test the characteristics of the products, before starting application.
- After use, keep the containers well closed.

IMPORTANT NOTE

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us to the suitability of the product for the intended purpose, does so at his own risk.

While we endeavour to ensure that all advice we give about the product is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product.

Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising from the performance of the product or for any loss or damage arising out of the use of the product.

The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.